

AD-A082 762 CINCINNATI UNIV OH DEPT OF ENGINEERING SCIENCE F/6 20/11  
MULTI-BODY DYNAMICS INCLUDING THE EFFECTS OF FLEXIBILITY AND CO-ETC(U)  
APR 80 R L HUSTON N00014-76-C-0139  
UNCLASSIFIED UC-ES-040180-8-ONR NL

F/G 20/11

APR 80 R L HUSTON

**N00014-76-C-0139**

UC-ES-040180-8-ONR

NL


1. 1. 1.

END

GATE

580

DTIC



0

10

11) 1 APR 1980

⑦ Technician, J. E. Sp. 72-21 Feb 24

DTIC  
ELECTE  
APR 7 1980

A

111 NR-EL-040180-2-11

Location #112

## DISTRIBUTION STATEMENT A

Approved for public release;  
Distribution Unlimited

15

410649

21

# A B S T R A C T

New and recently developed concepts and ideas useful in obtaining efficient computer algorithms for solving the equations of motion of multi-body mechanical systems with flexible links are presented and discussed. These ideas include the use of Euler parameters, Lagrange's form of d'Alembert's principle, generalized speeds, quasi-coordinates, relative coordinates, structural analysis techniques and body connection arrays. The mechanical systems considered are linked bodies forming a tree structure, but with no "closed loops" permitted. An explicit formulation of the equations of motion is presented.

Author	
Title	
Subject	
Indexing	
Classification	
Abstract	
Notes	
References	
Other	
Final	
A	

## INTRODUCTION

This report discusses the development of new methods for including the effects of flexibility and link and joint compliance in the governing dynamical equations of multi-body systems. Specifically, new, computationally-oriented techniques with potential for efficient, automated, and comprehensive analyses of multi-body system dynamics are presented and discussed.

The development of equations of motion of multi-body mechanical systems has received considerable attention of analysts in recent years. There are several reasons for this: Foremost, is the fact that many mechanical systems and devices can be effectively modelled by systems of linked bodies. But, another reason is the fact that it has just recently been possible with the aid of high-speed digital computers, to obtain efficient numerical solutions of the governing dynamical equations. Hence, the emphasis of researchers and analysts working with multi-body systems has been the formulation of equations of motion which can easily be developed into numerical algorithms for a computer code.

Most of the recent efforts in obtaining these dynamic formulations and their corresponding computational algorithms has been with systems of linked rigid bodies. Recently, however, a few researchers have attempted to include the effects of flexibility, compliance, and relative translation of the links by using a variety of approaches such as quasi-static methods, finite-element methods, modal analysis, and the strategic positioning of the flexible bodies, (for example, to the extremities of the system). Many of these efforts and the corresponding methodologies have been stimulated and motivated by specific application areas such as mechanism vibration and flexible satellite oscillations. In this report, these ideas are used and extended in the outline of new procedures for efficiently modelling the dynamics of multi-body systems with flexible links and joints.

I.

If a mechanical system consists of connected bodies such that no closed loops or circuits are formed, the system is called a "general-chain", "open-chain", or "open-tree" system. Figure 1. depicts such a system. References [1-81]\* provide summary of approaches taken to obtain efficient, computer-oriented formulation of equations of motion for such systems and related systems. If the mechanical system model of Figure 1. is generalized to include translation and compliance at the joints, it might appear as shown in Figure 2. References 2-143 provide a summary of approaches taken to include the effects of flexibility, translation, and link and joint compliance of these systems.

In one of these approaches it is shown [28, 29, 37, 38, 39, 51] that it is possible to obtain expressions for the governing equations in a form where the coefficients are directly related through computer algorithms. This approach uses Lagrange's form of d'Alembert's principle, as exposted by Kane and others [30, 52, 144, 145, 146] together with body connection arrays [37, 38, 39] and relative orientation coordinates [31, 32, 37, 50] to obtain the governing equations. Lagrange's form of d'Alembert's principle - a virtual work type approach combines the computational advantages of both Newton's laws and Lagrange's equations. That is, it has the advantage of automatic elimination of non-working internal constraint forces but without the introduction of tedious differentiation or other similar calculations.

Recently, it has been suggested by Huston, et. al. [32, 33, 37] that further efficiencies could be obtained through the use of Euler parameters as described by Whittaker [146] and Kane and Likins [147], together with the quasi-coordinates suggested by Kane and Wang [148]. Specifically, it is claimed [32, 33, 37] that using Euler parameters together with relative angular velocity components as generalized coordinate derivatives allows for the avoidance of geometrical singu-

\* Numbers in brackets refer to References at the end of the report.




Figure 1. A General Chain System




Figure 2. A General Chain System with Translation Between the Bodies



larities encountered with using Euler angles or dextral orientation angles to define the relative orientation of the bodies.

The use of Lagrange's form of d'Alembert's principle, body connection arrays, relative orientation coordinates, quasi-coordinates, and Euler parameters also promises to provide an effective and efficient approach in the modelling, governing equation formulation, and analysis of multi-body systems with flexible links and joints. The exposition of these ideas is a primary objective of this report.

The balance of the report is divided into five parts with the first two parts containing the geometrical and kinematical development. The governing dynamical equations are developed in the third part. This is followed by an analysis of the flexibility and compliance effects in the fourth part. The final part contains a discussion of the developed procedure together with concluding remarks.

## PRELIMINARY GEOMETRICAL CONSIDERATIONS

### Body Connection Array

Consider a mechanical system such as depicted in Figure 1. To develop an accounting routine for the system's geometry arbitrarily select one of the bodies as a reference body and call it  $B_1$ . Next, number or label the other bodies of the system in ascending progression away from  $B_1$  as shown in Figure 1. Now, although this numbering procedure does not lead to a unique labeling of the bodies, it can nevertheless be used to describe the chain structure or topology through the "body connection array" as follows: Let  $L(k)$ ,  $k=1, \dots, N$  be an array of the adjoining lower numbered body of body  $B_k$ . For example, for the system shown in Figure 1.,  $L(k)$  is:

$$L(k) = (0, 1, 1, 3, 1, 5, 6, 7, 6) \quad (1)$$

where

$$(k) = (1, 2, 3, 4, 5, 6, 7, 8, 9) \quad (2)$$

and where 0 refers to an inertial reference frame  $R$ . It is not difficult to see that, given  $L(k)$ , one could readily describe the topology of the system. That is, Figure 1. could be drawn by simply knowing  $L(k)$ . It is shown in the sequel that  $L(k)$  is useful in the development of expressions of kinematical quantities needed for analysis of the system's dynamics.

### Transformation Matrices

Next, consider a typical pair of adjoining bodies such as  $B_j$  and  $B_k$  as shown in Figure 3. The general orientation of  $B_k$  relative to  $B_j$  may be defined in terms of the relative orientation of the dextral orthogonal unit vector sets  $\underline{n}_{ji}$  and  $\underline{n}_{ki}$  ( $i=1,2,3$ ) fixed in  $B_j$  and  $B_k$  as shown in Figure 2. Specifically  $\underline{n}_{ji}$  and  $\underline{n}_{ki}$  are related to each other as

$$\underline{n}_{ji} = \text{SJK}_{im} \underline{n}_{km} \quad (3)$$

where SJK is a  $3 \times 3$  orthogonal transformation matrix defined as [47]:

$$\text{SJK}_{im} = \underline{n}_{ji} \cdot \underline{n}_{km} \quad (4)$$

(Regarding notation, the J and K in SJK and the first subscripts on the unit vectors refer to bodies  $B_j$  and  $B_k$ , and repeated indices, such as the m, in Equation (3) signify a sum over the range (eg. 1,...,3) of that index. Thus, with a computer  $\text{SJK}_{im}$  would be the array  $\text{SJK}(I,M)$ .)

From Equation (3), it is easily seen that with three bodies  $B_j$ ,  $B_k$ ,  $B_l$ , the transformation matrix obeys the following chain and identity rules:

$$\text{SJL} = \text{SJK SKL} \quad (5)$$




Figure 3. Two Typical Adjoining Bodies

and

$$SJJ = I = SJK SKJ = SJK SJK^{-1} \quad (6)$$

where I is the identity matrix.

These expressions allow for the transformation of components of vectors referred to one body of the system into components referred to any other body of the system and, in particular, to the inertial reference frame, R. For example, if a typical vector,  $\underline{V}$ , is expressed as

$$\underline{V} = v_i^{(k)} \underline{n}_{ki} = v_i^{(0)} \underline{n}_{0i} \quad (7)$$

then

$$v_i^{(0)} = SOK_{ij} v_j^{(k)} \quad (8)$$

where 0 refers to the inertial frame, R.

Since these transformation matrices play a central role throughout the analysis, it is helpful to also have an algorithm for their derivative, especially the derivative of SOK. Using Equation (3), and noting that  $\underline{n}_{0i}$  are fixed in R, the following is obtained:

$$d(SOK_{ij})/dt = \underline{n}_{0i} \cdot {}^R d \underline{n}_{kj} / dt \quad (9)$$

where the  $R$  in  $\frac{d}{dt} \underline{n}_{kj}$  indicates that the derivative is computed in  $R$ . However, since the  $\underline{n}_{kj}$  are fixed in  $B_k$ , their derivatives may be written as  $\underline{\omega}_k \times \underline{n}_{kj}$  where  $\underline{\omega}_k$  is the angular velocity of  $B_k$  in  $R$ . Equation (9) may then be written as:

$$d(SOK_{ij})/dt = -e_{imn} \omega_{kn} \underline{n}_{0m} \cdot \underline{n}_{kj} \quad (10)$$

or as

$$d(SOK)/dt = WOK SOK \quad (11)$$

where WOK is a matrix defined as

$$WOK_{im} = -e_{imn} \omega_{kn} \quad (12)$$

and where  $\omega_{kn}$  are the components of  $\underline{\omega}_k$  referred to  $\underline{n}_{0n}$  and  $e_{imn}$  is the standard permutation symbol [150]. (WOK is simply the matrix whose dual vector [150] is  $\underline{\omega}_k$ .) Equation (11) thus shows that the transformation matrix derivative may be computed by a simple matrix multiplication.

### Euler Parameters

Finally, consider describing the relative orientation of  $B_j$  and  $B_k$  by using the so-called Euler parameters as discussed by Whittaker [147] and Kane and Likins [148]. It is well known [147] that  $B_k$  may be brought into any

general orientation relative to  $B_j$  by means of a single rotation about an appropriate axis. If  $\underline{\lambda}_k$  is a unit vector along this axis and if  $\theta_k$  is the rotation angle, the four Euler parameters describing the orientation of  $B_k$  relative to  $B_j$  may be defined as:

$$\begin{aligned}\epsilon_{k1} &= \lambda_{k1} \sin(\theta_k/2) \\ \epsilon_{k2} &= \lambda_{k2} \sin(\theta_k/2) \\ \epsilon_{k3} &= \lambda_{k3} \sin(\theta_k/2) \\ \epsilon_{k4} &= \cos(\theta_k/2)\end{aligned}\tag{13}$$

where the  $\lambda_{ki}$  ( $i=1,2,3$ ) are the components of  $\underline{\lambda}_k$  referred to  $\underline{n}_{ji}$ , the unit vectors fixed in  $B_j$ . Clearly, the  $\epsilon_{ki}$  ( $i=1,2,3,4$ ) are not independent since:

$$\epsilon_{k1}^2 + \epsilon_{k2}^2 + \epsilon_{k3}^2 + \epsilon_{k4}^2 = 1\tag{14}$$

These parameters may be related to angular velocity components by using the transformation matrices as follows: It is shown in [147, 148] that SJK may be expressed in terms of these parameters as:

$$SJK = \begin{bmatrix} \epsilon_{k1}^2 - \epsilon_{k2}^2 - \epsilon_{k3}^2 + \epsilon_{k4}^2 & 2(\epsilon_{k1}\epsilon_{k2} - \epsilon_{k3}\epsilon_{k4}) & 2(\epsilon_{k1}\epsilon_{k3} + \epsilon_{k2}\epsilon_{k4}) \\ 2(\epsilon_{k1}\epsilon_{k2} + \epsilon_{k3}\epsilon_{k4}) & -\epsilon_{k1}^2 + \epsilon_{k2}^2 - \epsilon_{k3}^2 + \epsilon_{k4}^2 & 2(\epsilon_{k2}\epsilon_{k3} - \epsilon_{k1}\epsilon_{k4}) \\ 2(\epsilon_{k1}\epsilon_{k3} - \epsilon_{k2}\epsilon_{k4}) & 2(\epsilon_{k2}\epsilon_{k3} + \epsilon_{k1}\epsilon_{k4}) & -\epsilon_{k1}^2 - \epsilon_{k2}^2 + \epsilon_{k3}^2 + \epsilon_{k4}^2 \end{bmatrix} \quad (15)$$

Now, by solving Equations (11) and (12) for the angular velocity components, one obtains:

$$\begin{aligned} \omega_{k1} &= SOK_{21} \dot{SOK}_{31} + SOK_{22} \dot{SOK}_{32} + SOK_{23} \dot{SOK}_{33} \\ \omega_{k2} &= SOK_{31} \dot{SOK}_{11} + SOK_{32} \dot{SOK}_{12} + SOK_{33} \dot{SOK}_{13} \\ \omega_{k3} &= SOK_{11} \dot{SOK}_{21} + SOK_{12} \dot{SOK}_{22} + SOK_{13} \dot{SOK}_{23} \end{aligned} \quad (16)$$

where the dot designates time differentiation. By using Equation (15), these expressions may be used to express the  $\underline{n}_{ji}$  components of the angular velocity of  $B_k$  relative to  $B_j$  in terms of the Euler parameters as:

$$\begin{aligned} \hat{\omega}_{k1} &= 2(\epsilon_{k4} \dot{\epsilon}_{k1} - \epsilon_{k3} \dot{\epsilon}_{k2} + \epsilon_{k2} \dot{\epsilon}_{k3} - \epsilon_{k1} \dot{\epsilon}_{k4}) \\ \hat{\omega}_{k2} &= 2(\epsilon_{k3} \dot{\epsilon}_{k1} + \epsilon_{k4} \dot{\epsilon}_{k2} - \epsilon_{k1} \dot{\epsilon}_{k3} - \epsilon_{k2} \dot{\epsilon}_{k4}) \\ \hat{\omega}_{k3} &= 2(-\epsilon_{k2} \dot{\epsilon}_{k1} + \epsilon_{k1} \dot{\epsilon}_{k2} + \epsilon_{k4} \dot{\epsilon}_{k3} - \epsilon_{k3} \dot{\epsilon}_{k4}) \end{aligned} \quad (17)$$



(Regarding notation, in the sequel "hats" refer to relative angular velocity vectors or their components. That is the  $\underline{\omega}_k$  represent the angular velocity of  $B_k$  in  $R$  and  $\hat{\omega}_k$  represent the angular velocity of  $B_k$  relative to  $B_j$ , its adjoining lower numbered body.) Equation (17) may now be solved for the  $\hat{e}_{ki}$  ( $i=1, \dots, 4$ ) in terms of the  $\hat{\omega}_{ki}$ , leading to the expressions:

$$\begin{aligned}
 \dot{\hat{e}}_{k1} &= \frac{1}{2}(\epsilon_{k4} \hat{\omega}_{k1} + \epsilon_{k3} \hat{\omega}_{k2} - \epsilon_{k2} \hat{\omega}_{k3}) \\
 \dot{\hat{e}}_{k2} &= \frac{1}{2}(-\epsilon_{k3} \hat{\omega}_{k1} + \epsilon_{k4} \hat{\omega}_{k2} + \epsilon_{k1} \hat{\omega}_{k3}) \\
 \dot{\hat{e}}_{k3} &= \frac{1}{2}(\epsilon_{k2} \hat{\omega}_{k1} - \epsilon_{k1} \hat{\omega}_{k2} + \epsilon_{k4} \hat{\omega}_{k3}) \\
 \dot{\hat{e}}_{k4} &= \frac{1}{2}(-\epsilon_{k1} \hat{\omega}_{k1} - \epsilon_{k2} \hat{\omega}_{k2} - \epsilon_{k3} \hat{\omega}_{k3})
 \end{aligned} \tag{18}$$

This solution is quickly obtained by observing that if Equation (14) is differentiated and placed with Equation (17), the resulting set of equations could be written in the matrix form:

$$\begin{bmatrix} \hat{\omega}_{k1} \\ \hat{\omega}_{k2} \\ \hat{\omega}_{k3} \\ \hat{\omega}_{k4} \end{bmatrix} = 2 \begin{bmatrix} \epsilon_{k4} & -\epsilon_{k3} & \epsilon_{k2} & -\epsilon_{k1} \\ \epsilon_{k3} & \epsilon_{k4} & -\epsilon_{k1} & -\epsilon_{k2} \\ -\epsilon_{k2} & \epsilon_{k1} & \epsilon_{k4} & -\epsilon_{k3} \\ \epsilon_{k1} & \epsilon_{k2} & \epsilon_{k3} & \epsilon_{k4} \end{bmatrix} \begin{bmatrix} \dot{\hat{e}}_{k1} \\ \dot{\hat{e}}_{k2} \\ \dot{\hat{e}}_{k3} \\ \dot{\hat{e}}_{k4} \end{bmatrix} \tag{19}$$

where  $\omega_{k4}$  is equal to the derivative of Equation (14) and has the value zero. The square matrix in Equation (19) is seen to be orthogonal (ie. the inverse is the transpose) and hence, Equations (18) follow immediately from (19) upon letting  $\omega_{k4}$  be zero.

## KINEMATICS

### Coordinates

A multibody system of  $N$  bodies, with translation permitted between the bodies will, in general, have  $6N$  degrees of freedom. Let these be described by  $6N$  generalized coordinates  $x_l$  ( $l=1, \dots, 6N$ ) and let the first  $3N$  of these be divided into  $N$  triplets describing the relative orientation of the successive bodies of the system. Let the remaining  $3N$   $x_l$  also be divided into  $N$  triplets representing the relative displacement of the successive bodies of the system. As before, let  $B_k$  be a typical body of the system and let  $B_j$  be its adjacent lower numbered body, as in Figure 3. The angular velocity of  $B_k$  relative to  $B_j$  (that is, the relative rate of change of orientation) may then be written as:

$$\hat{\omega}_k = \hat{\omega}_{k1} \underline{n}_{j1} + \hat{\omega}_{k2} \underline{n}_{j2} + \hat{\omega}_{k3} \underline{n}_{j3} \quad (20)$$

where  $\underline{n}_{ji}$  ( $j=1, \dots, N$   $i=1,2,3$ ) are mutually perpendicular dextral unit vectors fixed in  $B_j$ . Next, let these bodies be displaced relative to each other with the displacement measured by the vector  $\underline{\xi}_k$  as shown in Figure 4., where  $O_j$  and  $O_k$  are arbitrarily selected reference points of  $B_j$  and  $B_k$ .  $O_k$ , which is fixed in  $B_j$ , is the connection point or "origin" of  $B_k$ . Then  $\underline{\xi}_k$  may be written in the form:




Figure 4. Reference Points and Position Vectors  
of Two Typical Adjoining Bodies

$$\dot{\xi}_k = \xi_{k1} \dot{n}_{j1} + \xi_{k2} \dot{n}_{j2} + \xi_{k3} \dot{n}_{j3} \quad (21)$$

Following Kane and Wang [149] introduce  $6N$  parameters  $y_l$  ( $l=1, \dots, 6N$ ) defined as:

$$y_l = \dot{x}_l \quad l = 1, \dots, 6N \quad (22)$$

where the first  $3N$  of these are called "generalized speeds", are

$$\begin{aligned} y_{3k-2} &= \hat{\omega}_{k1} \\ y_{3k-1} &= \hat{\omega}_{k2} \\ y_{3k} &= \hat{\omega}_{k3} \end{aligned} \quad (23)$$

and the remaining  $3N$  are:

$$\begin{aligned} y_{3(N+k)-2} &= \dot{\xi}_{k1} \\ y_{3(N+k)-1} &= \dot{\xi}_{k2} \\ y_{3(N+k)} &= \dot{\xi}_{k3} \end{aligned} \quad (24)$$

In general, Equations (23) are non-integrable. That is, they cannot be integrated to obtain generalized orientation coordinates  $x_{3k-2}$ ,  $x_{3k-1}$ ,  $x_{3k}$ . Thus, explicit parameters  $x_{3k-2}$ ,  $x_{3k-1}$ , and  $x_{3k}$  do not in general exist—hence, the name "quasi-coordinates". However, since parameters are needed to relate the relative orientation of the bodies to the respective relative angular velocities, let the Euler parameters introduced in the foregoing section be used for this purpose. Hence, if the orientation of a typical body  $B_k$  relative to  $B_j$  is described by the four parameters  $\epsilon_{ki}$  ( $i=1,\dots,4$ ), the geometry and kinematics of the entire system may be expressed in terms of the  $4N$  Euler parameters  $\epsilon_{ki}$  ( $k=1,\dots,N$ ;  $i=1,\dots,4$ ), the  $3N$  relative angular velocity components  $\hat{\omega}_{ki}$  ( $k=1,\dots,N$ ;  $i=1,2,3$ ), and the  $3N$  displacement components  $\xi_{ki}$  ( $k=1,\dots,N$ ;  $i=1,2,3$ ).

#### Angular Velocity

The angular velocity of a typical body  $B_k$  in the inertial frame  $R$  is readily obtained by the addition formula as [145]

$$\underline{\omega}_k = \hat{\omega}_1 + \dots + \hat{\omega}_k \quad (25)$$

where the relative angular velocities on the right side of this expression are each with respect to the respective adjacent lower numbered bodies and where the sum is taken over the bodies of the chain from  $B_1$  outward through the branch containing  $B_k$ . The  $L(k)$  array introduced in the foregoing section can be useful in computing this sum: Consider for example, the system shown in Figure 1. The angular velocity of  $B_9$  is:

$$\omega_9 = \hat{\omega}_1 + \hat{\omega}_5 + \hat{\omega}_6 + \hat{\omega}_9 \quad (26)$$

The subscript indices (ie. 9,6,5,1) may be obtained from  $L(k)$  as follows: Consider  $L(k)$  as a function mapping the  $(k)$  array (See Equation (2)) into the  $L(k)$  array. Then, using the notation that  $L^0(k) = (k)$ ,  $L^1(k) = L(L^0(k))$ ,  $L^2(k) = L(L^1(k))$ , ...,  $L^j(k) = L(L^{j-1}(k))$ , it is seen (see Equation (1)) that:

$$L^0(9) = 9, L^1(9) = 6, L^2(9) = 5, L^3(9) = 1 \quad (27)$$

Therefore,  $\omega_9$  may be written as:

$$\omega_9 = \sum_{p=0}^3 \hat{\omega}_q, \quad q = L^p(9) \quad (28)$$

Hence, in general, the angular velocity of  $B_k$  may be written as:

$$\omega_k = \sum_{p=0}^r \hat{\omega}_q, \quad q = L^p(k) \quad (29)$$

where  $r$  is the index such that  $L^r(k) = 1$  and it is obtained by comparing  $L^p(k)$  to 1. The index  $r$  represents the number of bodies from  $B_1$  to  $B_k$  in that branch of the chain system  $B_k$ . For example, for the system of Figure 1., if  $k=9$ ,  $r=3$ . Equation (29) is thus an algorithm for determining  $\omega_k$  once  $\hat{\omega}_k$  and  $L(k)$  are known.

By examining Equations (20), (23), and (25) it is seen that  $\omega_k$  may be written in the form

$$\omega_k = \omega_{klm} y_l \underline{n}_{0m} \quad (30)$$

where there is a sum over the repeated indices and where  $\omega_{klm}$  ( $k=1, \dots, N$ ;  $l=1, \dots, 3N$ ;  $m=1, 2, 3$ ) form a block array of coefficients needed to express  $\omega_k$  in terms of  $\underline{n}_{0m}$ . In view of Equations (3), (16), (20), and (23), it is seen that the elements of the  $\omega_{klm}$  array may be obtained from the SOK transformation matrices. Moreover, it can be shown that the matching between the elements of the  $\omega_{klm}$  and SOK arrays is solely dependent upon the body connection array  $L(k)$ .

To see this, consider for example the angular velocity of  $B_4$  of the system of Figure 1: From Equation (25),  $\omega_4$  is

$$\omega_4 = \hat{\omega}_1 + \hat{\omega}_3 + \hat{\omega}_4 \quad (31)$$

where from Equations (3), (20), and (23)  $\hat{\omega}_1$ ,  $\hat{\omega}_3$ , and  $\hat{\omega}_4$  may be written as:

$$\hat{\omega}_1 = y_1 \underline{n}_{01} + y_2 \underline{n}_{02} + y_3 \underline{n}_{03} = y_j \delta_{mj} \underline{n}_{0m} \quad (32)$$

$$\hat{\omega}_3 = y_7 \underline{n}_{11} + y_8 \underline{n}_{12} + y_9 \underline{n}_{13} = y_{6+j} S_{01}^{01}_{mh} \underline{n}_{0m} \quad (33)$$

$$\hat{\omega}_4 = y_{10} \underline{n}_{31} + y_{11} \underline{n}_{32} + y_{12} \underline{n}_{33} = y_{9+j} S_{03}^{03}_{mj} \underline{n}_{0m} \quad (34)$$



Hence, the  $\omega_{4lm}$  are:

$$\begin{aligned}
 &\delta_{ml} \quad l = 1, 2, 3 \\
 &0 \quad l = 4, 5, 6 \\
 &\omega_{4lm} = S01_{ml-9} \quad l = 7, 8, 9 \quad m = 1, 2, 3 \quad (35) \\
 &S03_{ml-9} \quad l = 10, 11, 12 \\
 &0 \quad l > 12
 \end{aligned}$$

where  $\delta_{ij}$  are the identity matrix components [150].

Next, consider that the results such as Equation (35) may be obtained for the entire system of Figure 1. or Figure 2. from a table such as Table 1., where the "m" entries of the  $\omega_{klm}$  array are the column of the transformation matrices. Finally, note that the non-zero entries in a typical row, say the  $k^{th}$  row of Table 1. are obtained as follows: Let  $P = L(k)$ . Then SOP is placed in the  $k^{th}$  column of triplets of  $\dot{x}_2$ . Next, let  $Q = L(P)$ . The SOQ is placed in the  $P^{th}$  column to triplets of  $\dot{x}_2$ , etc. That is, SOM is placed in column  $L^{j-1}(k)$  where  $M = L^j(k)$ ,  $j=1, \dots, r+1$  with  $r$  determined from  $L^r(k) = 1$ .

Finally, it is interesting to note that the elements of the  $\omega_{klm}$  array (and hence, the transformation matrix columns of Table 1.) are components of the "partial angular velocity vectors" as originally defined by Kane [144].

$\omega_{k\ell m}$ 

$\begin{smallmatrix} k \\ \ell \end{smallmatrix}$	1,2,3	4,5,6	7,8,9	10,11,12	13,14,15	16,17,18	19,20,21	22,23,24	25,26,27
1	I	0	0	0	0	0	0	0	0
2	I	S01	0	0	0	0	0	0	0
3	I	0	S01	0	0	0	0	0	0
4	I	0	S01	S03	0	0	0	0	0
5	I	0	0	0	S01	0	0	0	0
6	I	0	0	0	S01	S05	0	0	0
7	I	0	0	0	S01	S05	S06	0	0
8	I	0	0	0	S01	S05	S06	S07	0
9	I	0	0	0	S01	S05	0	0	S06

Table 1.  $\omega_{k\ell m}$  for the System of Figure 1.

### Angular Acceleration

The angular acceleration of  $B_k$  in  $R$  may be obtained by differentiating Equation (30). Noting that the  $\underline{n}_{om}$  are constant, this leads to:

$$\underline{\alpha}_k = (\dot{\omega}_{klm} \underline{y}_l + \omega_{klm} \dot{\underline{y}}_l) \underline{n}_{om} \quad (36)$$

A table containing the  $\dot{\omega}_{klm}$  can be constructed directly from the corresponding table for the  $\omega_{klm}$ . For example, for the system of Figure 1., such a table is shown in Table 2.

### Mass Center Velocities

The velocity and acceleration of the mass center  $G_k$  of a typical body  $B_k$  ( $k=1, \dots, N$ ) may be obtained as follows: Let  $\underline{r}_k$  locate  $G_k$  relative to  $O_k$  as shown in Figure 4. Since  $O_k$  is located relative to  $O_j$  by  $\underline{\xi}_k$  and if  $O_j$  is located relative to  $O_i$  by the vector  $\underline{q}_j$  (See Figure 4.), then by continuing this procedure,  $G_k$  may ultimately be located relative to a fixed point  $O$  in  $R$ , the inertial reference frame. For example, for Body  $B_8$  of Figure 2., the position vector  $\underline{P}_8$  of  $G_8$  relative to  $O$  is:

$$\underline{P}_8 = \underline{\xi}_1 + \underline{q}_5 + \underline{\xi}_5 + \underline{q}_6 + \underline{\xi}_6 + \underline{q}_7 + \underline{\xi}_7 + \underline{q}_8 + \underline{\xi}_8 + \underline{r}_8 \quad (37)$$

In general, for Body  $B_k$ , the position vector  $\underline{P}_k$  of  $G_k$  relative to  $O$  is:

$\dot{\omega}_{klm}$ 

$\frac{x_l}{k}$	1,2,3	4,5,6	7,8,9	10,11,12	13,14,15	16,17,18	19,20,21	22,23,24	25,26,27
1	0	0	0	0	0	0	0	0	0
2	0	s01	0	0	0	0	0	0	0
3	0	0	s01	0	0	0	0	0	0
4	0	0	s01	s03	0	0	0	0	0
5	0	0	0	0	s01	0	0	0	0
6	0	0	0	0	s01	s05	0	0	0
7	0	0	0	0	s01	s05	s06	0	0
8	0	0	0	0	s01	s05	s06	s07	0
9	0	0	0	0	s01	s05	0	0	s06

Table 2.  $\dot{\omega}_{klm}$  for the System of Figure 1.

$$\underline{p}_k = [\dot{S}O\dot{K}_{ih} r_{kh} + \sum_{q=0}^u \dot{S}O\dot{S}_{ih} (q_{sh} + \xi_{sh})] \underline{n}_{oi} \quad (38)$$

where  $s = L^q(k)$ ,  $S = L^{q+1}(k)$ , and  $u$  is the index such that  $L^u(k) = 1$ , and where  $q_1$  is 0. By differentiating, the velocity of  $G_k$  in  $R$  is obtained as:

$$\begin{aligned} \underline{v}_k = & \{ \dot{S}O\dot{K}_{ih} r_{ks} + \sum_{q=0}^u [\dot{S}O\dot{S}_{ih} (q_{sh} + \xi_{sh}) \\ & + \dot{S}O\dot{S}_{ih} \dot{\xi}_{sh}] \underline{n}_{oi} \end{aligned} \quad (39)$$

By using Equations (11), (12), and (30),  $\underline{v}_k$  may be written in the form:

$$\underline{v}_k = v_{klm} y_l \underline{n}_{om} \quad (40)$$

where  $v_{klm}$  ( $k=1, \dots, N$ ;  $l=1, \dots, 6N$ ;  $m=1, 2, 3$ ) form a block array of coefficients needed to express  $\underline{v}_k$  in terms of  $\underline{n}_{om}$ . In view of Equation (39), the non-zero  $v_{klm}$  are:

$$\begin{aligned} v_{klm} = & WK_{mhl} r_{kj} + \sum_{q=0}^u WS_{mhl} (\xi_{sh} + q_{sh}) \\ & (k=1, \dots, N; l=1, \dots, 3N; m=1, 2, 3) \end{aligned} \quad (41)$$

where  $WK_{mh}$  is defined as:

$$WK_{mhl} = \frac{\partial WOK_{mp}}{\partial y_l} \quad SOK_{ph} = -e_{mpi} \omega_{kli} SOK_{ph} \quad (42)$$

and

$$v_k(3N+l)m = \omega_{klm} \quad (k=1, \dots, N; \quad l=1, \dots, 3N; \quad m=1, 2, 3) \quad (43)$$

The elements of the  $v_{klm}$  array are components of the "partial velocity vectors" as originally defined by Kane [144].

#### Mass Center Accelerations

Similarly, by differentiation of Equations (40), the acceleration of  $G_k$  in  $R$  is

$$\underline{a}_k = (\dot{v}_{klm} y_l + v_{klm} \dot{y}_l) \underline{n}_{om} \quad (44)$$

where the non-zero  $\dot{v}_{klm}$  are, by Equations (41) to (43),

$$\dot{v}_{klm} = WK_{mhl} \dot{r}_{kh} + \sum_{q=0}^{u-1} [WS_{mhl} (\xi_{sh} + q_{sh}) + WS_{mhl} \xi_{sh}] \quad (k=1, \dots, N; \quad l=1, \dots, 3N, \quad m=1, 2, 3) \quad (45)$$

where  $WK_{mhl}$  is:

$$WK_{mhl} = -e_{mpi} (\dot{\omega}_{kli} SOK_{ph} + \omega_{kli} \dot{SOK}_{ph}) \quad (46)$$

and

$$\dot{v}_k(3N+l)_m = \dot{\omega}_{klm} \quad (k=1, \dots, N; \quad l=1, \dots, 3N, \quad m=1, 2, 3) \quad (47)$$

## EQUATIONS OF MOTION

Consider again a general chain system such as shown in Figure 2., and imagine the system to be subjected to an externally applied force field. Let the force field on a typical body  $B_k$ , be replaced by an equivalent force field consisting of a single force  $\underline{F}_k$ , passing through  $G_k$  together with a couple with torque  $\underline{M}_k$ . Then Lagrange's form of d'Alembert's principle leads to governing dynamical equations of motion of the form [38]:

$$\underline{F}_l + \underline{F}_l^* = 0 \quad l = 1, \dots, 6N \quad (48)$$

$\underline{F}_l$  ( $l=1, \dots, 6N$ ) is called the generalized active force and is given by:

$$\underline{F}_l = v_{klm} \underline{F}_{km} + \omega_{klm} \underline{M}_{km} \quad (49)$$

where there is a sum from 1 to  $N$  on  $k$  and from 1 to 3 on  $m$ , and where  $\underline{F}_{km}$  and  $\underline{M}_{km}$  are the components of  $\underline{F}_k$  and  $\underline{M}_k$  with respect to  $\underline{n}_{om}$ .  $\underline{F}_l^*$  ( $l=1, \dots, 6N$ ) is called the generalized inertia force and is given by:

$$\underline{F}_l^* = v_{klm} \underline{F}_{km}^* + \omega_{klm} \underline{M}_{km}^* \quad (50)$$



where the indices follow the same rules as in Equation (48), and where

$F_{km}^*$  and  $M_{km}^*$  are  $n_{om}$  components of inertia forces,  $F_k^*$ , and inertia torques,  $M_k^*$ , given by [145].

$$F_k^* = -m_k \ddot{a}_k \quad (\text{no sum}) \quad (51)$$

and

$$M_k^* = -I_k \cdot \ddot{\alpha}_k - \omega_k \times (I_k \cdot \omega_k) \quad (\text{no sum}) \quad (52)$$

where  $m_k$  is the mass of  $B_k$  and  $I_k$  is the inertia dyadic of  $B_k$  relative to  $G_k$  ( $k=1, \dots, N$ ). ( $F_k^*$ , with line of action passing through  $G_k$  together with  $M_k^*$  are equivalent to the inertia forces on  $B_k$  [145]. Through use of the shifter transformation matrices,  $I_k$  may be written in the form:

$$I_k = I_{kmm} \begin{matrix} n_{om} \\ n_{on} \end{matrix} \quad (53)$$

By substituting Equations (36) and (44) into Equations (51) and (52) and ultimately into Equation (47), the equations of motion may be written in the form:

$$a_{lp} \dot{y}_p = f_l \quad (l=1, \dots, 6N) \quad (54)$$

where there is a sum from 1 to 6N on p and where  $a_{lp}$  and  $f_l$  are given by:

$$a_{lp} = m_k v_{kpm} v_{klm} + I_{kmn} \omega_{kpm} \omega_{kln} \quad (55)$$

and

$$f_l = - (F_l + m_k v_{klm} v_{kqm} y_q + I_{kmn} \omega_{klm} \dot{\omega}_{kqn} y_q + e_{nmh} I_{kmr} \omega_{kqn} \omega_{ksr} \omega_{kln} y_q y_s) \quad (56)$$

where there is a sum from 1 to N on k, from 1 to 6N on q and s, and from 1 to 3 on the other repeated indices.

Recall that the first 3N  $y_p$  are relative angular velocity components. These may be related to the Euler parameters by N sets of first order equations of the form of Equations (18).

Equations (54), (20), and the 4N equations of the form of Equations (18) form a set of 13N simultaneous first-order differential equations for the 6N  $y_p$ , the 3N  $\xi_{ki}$ , and the 4N Euler parameters  $e_{ki}$  ( $h=1, \dots, N$ ;  $i=1, \dots, 4$ ). Since the coefficients  $a_{lp}$  and  $f_l$  in Equations (54) are algebraic functions of the physical parameters and the four block arrays  $\omega_{klm}$ ,  $\dot{\omega}_{klm}$ ,  $v_{klm}$  and  $\dot{v}_{klm}$ , computer algorithms can be written for the numerical development of these governing equations. Moreover, once these

arrays are developed, the system of equations consisting of Equations (54), (20), and  $4N$  equations of the form of Equations (18), may also be solved numerically by using one of the standard numerical integration routines and a linear equation solver.

The development of these computer algorithms and the numerical development of Equations (54) might proceed as follows: First, let the body connection array  $L(k)$  (See Equation (1)) together with the geometrical and physical parameters  $\underline{r}_k$ ,  $\underline{\xi}_k$ ,  $\underline{I}_k$ , and  $m_k$  (See Equations (38), (51), and (52).) and the applied forces and moments  $\underline{F}_k$  and  $\underline{M}_k$  (See Equation (48).) be read into the computer. (Let  $\underline{r}_k$ ,  $\underline{\xi}_k$ ,  $\underline{I}_k$  and, if desired,  $\underline{F}_k$  and  $\underline{M}_k$  be expressed in terms of  $\underline{n}_{ki}$ .) Next, from assumed initial values of  $\underline{e}_{ki}$  form the transformation matrix arrays  $SOK$  using Equations (15) and (5). Use these arrays to express  $\underline{r}_k$ ,  $\underline{\xi}_k$ ,  $\underline{I}_k$  and possibly  $\underline{F}_k$  and  $\underline{M}_k$  in terms of  $\underline{n}_{ok}$ . Next, using  $L(k)$  and  $SOK$  write an algorithm, with Tables 1. and 2. as a guide, to form  $\omega_{klm}$  and  $\dot{\omega}_{klm}$ . For example, to obtain the non-zero  $\omega_{klm}$ , observe that if  $L(k) = p$ , then  $\omega_{klm} = SOP_{ml}$  ( $m=1,2,3$ ;  $l=3p+1, 3p+2, 3p+3$ ). Then, if  $L(p) = q$ ,  $L^2(k) = q$  and  $\omega_{klm} = SOQ_m$  ( $m=1,2,3$ ;  $l=3q+1, 3q+2, 3q+3$ ). This assignment procedure is continued until unity is reached or  $r$  times where  $r$  is given by  $L^r(k) = 1$  (See the remark following Equation (29).).  $v_{klm}$  and  $\dot{v}_{klm}$  may then be obtained using Equations (40) to (47). Finally, numerical values of the coefficients  $a_{lp}$  and  $f_l$  of the governing differential equations (54) may then be obtained from Equations (55) and (56). These equations may then be integrated numerically to obtain incremental values to the initial values of the parameters  $y_p$ ,  $\underline{e}_{ki}$ , and  $x_q$  ( $p=1, \dots, 3N+3$ ;  $k=1, \dots, N$ ;  $i=1,2,3,4$  and  $q=1,2,3$ ), at the end of a time interval, say  $t_1$ . New values of the

transformation matrix arrays SOK may then be obtained and the entire process repeated until a history of the configuration and motion of the system is determined.

The application of these expressions and ideas in an analysis of the flexibility and compliance effects is developed in the following part of the report.

## EFFECTS OF COMPLIANCE AND FLEXIBILITY

### Compliance

Let the term "compliance" refer to the yielding or deformation of the system due to the externally applied forces and due to the inertia forces. If the assumption is made that the compliance of a link or joint is "small" compared with the general dimensions of the system, then the effects of the compliance can be determined directly from the integration of Equations (54).

To see this, consider a typical integration step as described at the end of the foregoing section. If the  $v_{k\ell m}$ ,  $\dot{v}_{k\ell m}$ ,  $\omega_{k\ell m}$ ,  $\dot{\omega}_{k\ell m}$ ,  $\epsilon_{ki}$ ,  $y_\ell$ , and  $\dot{y}_\ell$  are known, all the kinematics is known. That is, by using Equations (30) and (36) the angular velocity and angular acceleration of each body is determined. Similarly, by using Equations (40) and (44), the velocities and accelerations of the mass centers of each of the bodies is determined. Then, by using Equations (51) and (52) the equivalent inertia force system on each body is determined. Hence, since the externally applied force field on each body is also known, the entire force system on each body is determined. Therefore, by taking successive free body diagrams of the bodies of the system, starting with the Nth body and working backward through the chain, the force system transmitted across each connection joint may be determined. Finally, by knowing the complete force system acting on each body, including the forces transmitted across the connection joints, the physical force-deformation relations may be used to determine the compliance. Then by addition and superposition the compliance of the entire system is determined.

To illustrate this procedure in more detail, assume, for example, that the bodies of the system are long slender members which can be modelled as beams with uniform cross section. Hence, the system of Figures 1. and 2. might appear as

shown in Figure 5., and a typical member of this system might be depicted as in Figure 6., where a rectangular shape is assumed and where an axes system is introduced. As before  $O_j$  is the connection point of the adjacent lower numbered body  $B_i$  and  $Q_k$  is the connection point with the adjacent higher numbered body  $B_k$ .

Let the forces exerted on  $B_j$  by  $B_i$  and  $B_k$  at the connection joints  $O_j$  and  $Q_k$  be represented by single forces  $\hat{f}_{i/j}$  and  $\hat{f}_{k/j}$  passing through  $O_j$  and  $Q_k$  together with couples with torques  $\hat{m}_{i/j}$  and  $\hat{m}_{k/j}$ . Similarly, let the externally applied force system on  $B_j$  together with the inertia force system of  $B_j$  be represented by equivalent force systems at the ends  $O_j$  and  $Q_k$  of  $B_j$ . Hence, let the resultant force system exerted on  $B_j$  at  $Q_k$  be represented by the single force  $\hat{f}_{k/j}$  passing through  $Q_k$ , together with a couple with torque  $\hat{m}_{k/j}$  and let  $\hat{f}_{k/j}$  and  $\hat{m}_{k/j}$  be expressed in the forms:

$$\hat{f}_{k/j} = f_{j1} \hat{n}_{j1} + f_{j2} \hat{n}_{j2} + f_{j3} \hat{n}_{j3} \quad (57)$$

and

$$\hat{m}_{k/j} = m_{j1} \hat{n}_{j1} + m_{j2} \hat{n}_{j2} + m_{j3} \hat{n}_{j3}$$

(Note, that from equilibrium considerations, the force system exerted on  $B_j$  at  $O_j$  is equivalent to a single force  $-\hat{f}_{k/j}$  passing through  $O_j$  together with a couple with torque  $-\hat{m}_{k/j}$ .)

Let the displacement of  $Q_k$  relative to  $O_j$  due to the beam compliance, or deformation, be represented by  $\hat{u}_j$ . Let  $\hat{u}_j$  be written in the form:

$$\hat{u}_j = u_{j1} \hat{n}_{j1} + u_{j2} \hat{n}_{j2} + u_{j3} \hat{n}_{j3} \quad (59)$$

Similarly, let the rotation of the beam cross section at  $Q_k$  relative to the cross section at  $O_j$ , due to the beam compliance, be represented by  $\hat{\phi}_j$ . Let  $\hat{\phi}_j$  be




Figure 5. A General Chain System of Slender Members




Figure 6. A Typical Member of a Beam Chain System



written in the form:

$$\phi_j = \phi_{j1} \underline{u}_{j1} + \phi_{j2} \underline{u}_{j2} + \phi_{j3} \underline{u}_{j3} \quad (60)$$

By following the procedures of matrix structural analysis [15]  $u_{ji}$  and  $\phi_{ji}$  may be expressed in terms of  $f_{ji}$  and  $m_{ji}$  ( $i = 1, 2, 3$ ) as:

$$u_{j1} = (\ell_j / A_j E_j) f_{j1} \quad (61)$$

$$u_{j2} = (\ell_j^3 / 3E_j J_{j2}) f_{j2} + (\ell_j^2 / 2E_j J_{j2}) m_{j3} \quad (62)$$

$$u_{j3} = (\ell_j^3 / 3E_j J_{j3}) f_{j3} - (\ell_j^2 / 2E_j J_{j3}) m_{j2} \quad (63)$$

$$\phi_{j1} = (\ell_j / J_{j1} G_j) m_{j1} \quad (64)$$

$$\phi_{j2} = (\ell_j^2 / 2E_j J_{j2}) f_{j2} + (\ell_j / E_j J_{j2}) m_{j3} \quad (65)$$

$$\phi_{j3} = (\ell_j^2 / 2E_j J_{j3}) f_{j3} - (\ell_j / E_j J_{j3}) m_{j2} \quad (66)$$

where  $\ell_j$  is the axial length of  $B_j$ ,  $A_j$  is the cross-sectional area,  $J_{ji}$  ( $i = 1, 2, 3$ ) are the centroidal second moments of area of the cross section relative to the  $X_{ji}$  axes,  $E_j$  is the elastic modulus, and  $G_j$  is the shear modulus.

$\underline{u}_j$  and  $\underline{\phi}_j$  thus represent the compliance as yielding of member  $B_j$  due to the holding and system motion. In an automated analysis as outlined in the foregoing section,  $\underline{u}_j$  and  $\underline{\phi}_j$  would be calculated and then used to adjust the geometrical parameters at each integration step. Specifically,  $q_k$  (See Figure 4.) and SOK are adjusted as:

$$q_k \rightarrow q_k + \underline{u}_j \quad (67)$$

and

$$SOK \rightarrow SOK \text{ CJ} \quad (68)$$

where CK is

$$CJ = \begin{bmatrix} 1 & -\phi_{j3} & \phi_{j2} \\ \phi_{j3} & 1 & -\phi_{j1} \\ \phi_{j2} & \phi_{j1} & 1 \end{bmatrix} \quad (69)$$

(The development of Equation (69) follows from the successive multiplications of matrices of the form of Equation (15) for  $\theta$  being  $\phi_{jk}$ ,  $\phi_{j2}$ , and  $\phi_{j3}$  (small angles) about the  $X_{j1}$ ,  $X_{j2}$ , and  $X_{j3}$  axes respectively.) The integration would then proceed with the adjusted values of  $q_k$  and SOK.


### Vibration and Impact Response

The above compliance analysis is a quasi static analysis and as such it does not directly account for oscillatory or vibration phenomena due to the flexibility of the system and the externally applied (for example, impact) and inertia forces. If, as before, it is assumed that the vibrations have relatively small amplitude, then a modelling and description of the vibration phenomena may be obtained through torsion and translation springs introduced at the connection points, or joints, of the system.

To illustrate this, consider again a system consisting of long slender members which can be modelled as beams as in Figure 5. Consider two typical adjoining members of such a system as shown in Figure 7. The contribution to the systems oscillation due to the flexibility of  $B_j$  can be modelled by 1) three torsion springs connecting the surfaces of  $Q_k$  and  $O_k$  with spring constants  $G_j J_{j1}/\ell_j$ , and  $E_j J_{j3}/\ell_j$  and governing the relative rotation of  $B_j$  and  $B_k$  about axes parallel to  $n_{j1}$ ,  $n_{j2}$  and  $n_{j3}$  respectively; and by 2) three translation springs connecting  $Q_k$  and  $O_k$  with spring constants  $A_j E_j/\ell_j$ ,  $3E_j J_{j3}/\ell_j^3$  and  $3E_j J_{j2}/\ell_j^3$  and governing the relative translation of  $B_j$  and  $B_k$  along axes parallel to  $n_{j1}$ ,  $n_{j2}$ ,  $n_{j3}$ . (these constants are determined from elementary structural analysis as in Equations (61) to (66).)

### Discussion

Both of the above analyses involve the effects of forces and moments transmitted across connection joints. The dynamics analysis of the preceding part is



Torsion and translation springs

Figure 7. Two Typical Adjoining Slender Members

particularly well suited for accomodating the introduction of these forces and moments and for obtaining their contributions to the generalized forces. That is, although the compliance procedure above suggests the use of successive free body diagrams to obtain the force and moment components, and although this procedure could be automated, these components as well as the spring and moment components of the above oscillation analysis, can be readily obtained and directly incorporated into the governing equations by using the partial velocity and partial angular velocity vectors of the preceding dynamics analysis.

To see this, consider again two typical adjoining bodies such as  $B_j$  and  $B_k$  of Figures 4. and 7. As in Figure 4., let  $\xi_k$  measure the displacement of  $O_k$  relative to  $Q_k$ . Then by differentiation of  $\xi_k$  [145] the velocity of  $O_k$  may be expressed as:

$$\dot{v}^{O_k} = \dot{v}^{Q_k} + \omega_j \times \xi_k + \dot{\xi}_{ki} n_{ji} \quad (70)$$

As before, let the orientation and rotation of  $B_k$  relative to  $B_j$  be defined in terms of Euler parameters and relative angular velocity components. Then, from Equation (25) the angular velocity of  $B_k$  may be expressed as:

$$\omega_k = \omega_j + \hat{\omega}_k = \omega_j + \hat{\omega}_{ki} n_{ji} \quad (71)$$

Let the force system which  $B_k$  exerts on  $B_j$  be equivalent to a single force  $f_{k/j}$  passing through  $Q_k$  together with a couple with torque  $m_{k/j}$ , as in Equations (57) and (58). Then by the law of action-reaction, the force system which  $B_j$  exerts on  $B_k$  is equivalent to a single force  $-f_{k/j}$  passing through  $Q_k$  together with a couple with torque  $-m_{k/j}$ .

Let  $y_\ell$  ( $\ell=1, \dots, 6N$ ) be the generalized coordinate derivatives as defined by Equations (23) and (24). Let the contribution to the generalized active force  $F_\ell$  by these forces transmitted across the connecting joint be  $\hat{F}_\ell$ . Then  $\hat{F}_\ell$  is given by the expression [145]:

$$\begin{aligned}\hat{F}_\ell &= (\partial \underline{v}^{Q_k} / \partial y_\ell) \cdot (\underline{f}_{k/j}) + (\partial \underline{\omega}_j / \partial y_\ell) \cdot (\underline{m}_{k/j}) \\ &+ (\partial \underline{v}^{Q_k} / \partial y_\ell) \cdot (-\underline{f}_{k/j}) + (\partial \underline{\omega}_k / \partial y_\ell) \cdot (-\underline{m}_{k/j})\end{aligned}\quad (72)$$

Consider the following cases:

Case 1:  $y_\ell$  is not equal to either  $\xi_{ki}$  or  $\hat{\omega}_{ki}$ . In this case the partial velocities and partial angular velocities of  $Q_k$ ,  $O_k$ ,  $B_j$ , and  $B_k$  may be expressed by using Equations (70) and (71) as:

$$\partial \underline{v}^{Q_k} / \partial y_\ell = \partial \underline{v}^{Q_k} / \partial y_\ell \quad (73)$$

and

$$\partial \underline{\omega}_k / \partial y_\ell = \partial \underline{\omega}_j / \partial y_\ell \quad (74)$$

Then, by Equation (72),  $\hat{F}_\ell$  becomes:

$$\hat{F}_\ell = 0 \quad (75)$$

Case 2:  $y_\ell$  is equal to one of the  $\xi_{ki}$  ( $i=1, 2, 3$ ). In this case, the partial velocities and partial angular velocities of  $Q_k$ ,  $O_k$ ,  $B_j$ , and  $B_k$  become:

$$\partial \underline{v}^{Q_k} / \partial y_\ell = \partial \underline{v}^{Q_k} / \partial \xi_{ki} = 0 \quad (76)$$

$$\partial \underline{v}^{O_k} / \partial y_\ell = \partial \underline{v}^{O_k} / \partial \xi_{ki} = \underline{n}_{ji} \quad (77)$$

$$\partial \underline{\omega}_j / \partial y_\ell = \partial \underline{\omega}_j / \partial \xi_{ki} = 0 \quad (78)$$

and

$$\partial \underline{\omega}_k / \partial y_\ell = \partial \underline{\omega}_k / \partial \xi_{ki} = 0 \quad (79)$$

Hence, by Equation (72) and (57),  $\hat{F}_\ell$  becomes:

$$\hat{F}_\ell = \underline{n}_{ji} \cdot (-\underline{f}_{k/j}) = -\underline{f}_{ji} \quad (80)$$

Case 3:  $y_\ell$  is equal to one of the  $\hat{\omega}_{ki}$  ( $i=1, 2, 3$ ). In this case, the partial velocities and partial angular velocities of  $Q_k$ ,  $O_k$ ,  $B_j$ , and  $B_k$  become:

$$\partial \underline{v}^Q_k / \partial y_\ell = \partial \underline{v}^Q_k / \partial \hat{\omega}_{ki} = 0 \quad (81)$$

$$\partial \underline{v}^O_k / \partial y_\ell = \partial \underline{v}^O_k / \partial \hat{\omega}_{ki} = 0 \quad (82)$$

$$\partial \underline{\omega}_j / \partial y_\ell = \partial \underline{\omega}_j / \partial \hat{\omega}_{ki} = 0 \quad (83)$$

$$\partial \underline{\omega}_k / \partial y_\ell = \partial \underline{\omega}_k / \partial \hat{\omega}_{ki} = \underline{n}_{ji} \quad (84)$$

Hence, by Equation (72) and (53),  $\hat{F}_\ell$  becomes:

$$\hat{F}_\ell = \underline{n}_{ji} \cdot (-\underline{m}_{k/j}) = -\underline{m}_{ji} \quad (85)$$

The above three cases include the contribution to the generalized active forces for each of the  $y_\ell$  ( $\ell = 1, \dots, 6N$ ). Moreover, each of the non-zero contributions (from Equations (80) and (85)) occurs individually; that is, each contribution occurs separately in one of the governing equations. Hence, if in a particular configuration or motion of the system,  $y_\ell$  is specified (for example,  $y_\ell$  is zero) then the  $\ell$ th governing equation becomes an uncoupled linear expression for the unknown restraining force or moment, thus determining the compliance. Conversely, if  $y_\ell$  is an unknown variable (representing a degree of freedom) the contribution to  $F_\ell$  due to the flexibility as modelled by the translation and torsion springs is determined directly by Equations (61) to (66), (80), and (85).

## CONCLUDING REMARKS

The results of numerically solving the governing differential equations (54) where the coefficients are given by Equations (55) and (56) are reported and discussed in References [1, 32, 34, 35, 36, 77, 152-155] for a number of physical systems and configurations (e.g. human-body models, head-neck models, and flexible cables).

The application of Equations (54) with these systems, however, is based on the use of relative orientation angles between the respective bodies of the system as the generalized coordinates ( $x_\ell$ ) as opposed to the use of Euler parameters, quasi-coordinates, and generalized speeds as outlined herein. A problem which arises in the numerical solution of Equations (54) where orientation angles are used is that there always exists values of the angles and hence, configurations of the system, for which the determinant of  $a_{k\ell}$  is zero. A numerical solution will, of course, fail to converge at these singular configurations of the system, and convergence is very slow for configurations in the vicinity of a singularity. This problem is avoided by using Euler parameters to relate the orientation geometry to the angular velocity.

The advantages of using Lagrange's form of d'Alembert's principle to obtain the governing equations of motion for multi-body mechanical systems has been expounded in detail in References [28-30]. Basically, this principle has the advantages of Lagrange's equations or of virtual work in that non-working internal constraint forces, between the bodies of the system, are automatically eliminated from the analysis, and may therefore be ignored in the formulation of the governing equations. The principle, however, has the additional advantage of avoiding the

differentiation of scalar energy functions. Indeed, the differentiation required to obtain velocities and accelerations are performed by vector cross products and multiplication algorithms -- procedures which are ideally suited for numerical computation. As with Lagrange's equations, Lagrange's form of d'Alembert's principle requires the use of generalized coordinates to define the system geometry. The use of Euler parameters to avoid problems with singularities, as discussed above, leads naturally to the use of generalized speeds -- that is, relative angular velocity components as the generalized coordinate derivatives. This, in turn, leads to additional computational advantages as observed by Kane and Wang [149] and Likins [122]. Specifically, by using generalized speeds (relative angular velocity components) as the principle parameters of the analysis, the coefficient matrices in the governing equations can be obtained directly from the body connection array  $L(k)$  (see Tables 1. and 2.).

The use of "relative" coordinates, that is, angular velocity components of the bodies with respect to their adjoining bodies, as opposed to "absolute" coordinates, (for example, angular velocity components in inertial space) also contributes to the computational advantage. In applications with specific geometrical configurations [1, 31, 32, 34-36, 50, 77, 152-155], it is seen that the geometry is more easily described in terms of relative coordinates.

The generalization to allow translation between the bodies of the system makes the analysis applicable to a much broader class of problems than was possible with these previous analyses which are restricted to linked multi-body systems. For example, with the head-neck systems of References [152, 154, 155] the use of translation variables between the vertebrae is necessary to obtain satisfactory models of such systems. But, and of perhaps greater significance, the generalization to include translation between the bodies of the system is necessary for an efficient



analysis of the flexibility and compliance effects as discussed earlier.

In this regard, the compliance can be modelled with a quasi-static approach whereas the oscillations and impact response require a dynamic analysis with the introduction of additional degrees of freedom. In both of these cases the analysis outlined herein (using Lagrange's form of d'Alembert's principle together with the use of generalized speeds) accomodates the effects of flexibility in an extremely efficient manner. That is, the forces and moments transmitted across the system joints are directly determined and incorporated into the governing equations. Moreover, the modelling may be made as detailed as necessary by introducing nonlinearities through the elastic springs and dampers and by increasing the number of joints and bodies of the system.

Finally, the entire analysis outlined herein is developed with the intent of obtaining efficiencies in a computer oriented development of the governing dynamical equations. As such, its most productive application will be with large multi-body systems such as finite-segment models of the human body, chains, cables, robots, manipulators, and teleoperators.

## REFERENCES

1. Abdelnour, T. A., Passerello, C. E., and Huston, R. L., "An Analytical Analysis of Walking," ASME Paper No. 75-WA/Bio-4.
2. Allen, R. R., and Dubowsky, S., "Mechanisms as Components of Dynamic Systems: A Bond Graph Approach," ASME Paper No. 76-DET-21, Journal of Engineering for Industry, 1976.
3. Andrews, G. C., and Kesavan, H. K., "The Vector Network Model: A New Approach to Vector Dynamics," Mechanism and Machine Theory, Vol. 10, 1975, pp. 57-75.
4. Andrews, G. C., and Kesavan, H. K., "Simulation of Multibody Systems Using the Vector-Network Model," Dynamics of Multibody Systems, K. Magnus, Editor, Springer, 1977, pp. 1-13.
5. Bayazitoglu, Y. O., "Methods for Automated Analysis of Three-Dimensional Mechanical Dynamic Systems with Application to Nonlinear Vehicle Dynamics," PhD Dissertation, University of Michigan, 1972.
6. Bayazitoglu, Y. O., and Chace, M. A., "Methods of Automated Dynamic Analysis of Discrete Mechanical Systems," ASME Journal of Applied Mechanics, Vol. 40, 1973, pp. 809-819.
7. Bayazitoglu, Y. O., and Chace, M. A., "Dynamic Analysis of a Three-Dimensional Vehicle Model Undergoing Large Deflections," SAE Paper No. 770051, Informational Automotive Engineering Congress and Exposition, Detroit, 1977.
8. Benedict, C. E., and Tesar, D., "Model Formulation of Complex Mechanisms with Multiple Inputs: Part I - Geometry, Part II - The Dynamic Model," ASME Papers Nos. 77-WA/DE-9, 77-WA/DE-10, 1977.
9. Chace, M. A., "Analysis of the Time-Dependence of Multifreedom Mechanical Systems in Relative Coordinates," Journal of Engineering for Industry, pp. 119-125, February, 1967.

10. Chace, M. A., and Bayazitoglu, Y. O., "Development and Application of a Generalized d'Alembert Force for Multifreedom Mechanical Systems," Journal of Engineering for Industry, Vol. 93, pp. 317-327, 1971.
11. Chace, M. A., and Smith, D. A., "DAMN - Digital Computer Program for the Dynamic Analysis of Generalized Mechanical Systems," SAE Transactions, Vol. 80, pp. 969-983, 1971.
12. Chace, M. A., and Sheth, P. N., "Adaption of Computer Techniques to the Design of Mechanical Dynamic Machinery," ASME Paper No. 73-DET-58, 1973.
13. Chadwick, C. H., "On the Dynamics of Systems of Rigid Bodies Connected in Open Chains by Spherical and/or Revolute Joints," PhD Dissertation, Stanford University, 1972.
14. Chaffin, D. B., "A Computerized Biomechanical Model - Development of and Use in Studying Gross Body Actions," Journal of Biomechanics, Vol. 2, pp. 429-441, 1969.
15. Denavit, J., and Hartenberg, R. S., "A Kinematic Notation for Lower-Pair Mechanisms Based on Matrices," Journal of Applied Mechanics, pp. 215-221, June 1955.
16. Denavit, J., Hartenberg, R. S., Razi, R., and Uicker, J. J., Jr., "Velocity, Acceleration, and Static-Force Analysis of Spatial Linkages," Journal of Applied Mechanics, Vol. 32, pp. 903-910, 1965.
17. Dix, R. C., and Lehman, T. J., "Simulation of the Dynamics of Machinery," Journal of Engineering for Industry, Trans. ASME Ser. B., Vol. 94, pp. 433-438, 1972.
18. Fleischer, G. E., "Multirigid-Body Attitude Dynamics Simulation," Jet Propulsion Laboratory, Pasadena, Calif., Technical Report No. 32-1516, February 1971.
19. Frank, A. A., "An Approach to the Dynamic Analysis and Synthesis of Biped Locomotion Machines," Med. and Bio. Engineering, Vol. 8, pp. 465-476, 1970.
20. Frisch, H. P., "A Vector-Dyadic Development of the Equations of Motion of N Coupled Rigid Bodies and Point Masses," Goddard Space Flight Center, Greenbelt, Md., NASA TN D-7767, October 1974.

21. Galliday, C. L., Jr., and Hermani, H., "An Approach to Analyzing Biped Locomotion Dynamics and Designing Robot Locomotion Controls," IEEE Transactions on Automatic Control, Vol. AC-22, No. 6, pp. 963-972, December 1977.
22. Givens, E. J., and Walford, J. C., "Dynamic Characteristics of Spatial Mechanisms," Journal of Engineering for Industry, Vol. 91, pp. 228-234, 1969.
23. Gupta, V. K., "Dynamical Analysis of Multi-Rigid-Body Systems," Journal of Engineering for Industry, Vol. 96, pp. 886-892, 1974.
24. Hermami, H., and Jaswa, V. C., "On a Three-Link Model of the Dynamics of Standing Up and Sitting Down," IEEE Transactions on Systems, Man, and Cybernetics, Vol. SMC-8, No. 2, February 1978.
25. Ho, J. Y. L., Hooker, W. W., Margulies, G., and Winarske, T. P., "Remote Manipulator System Simulation, Volume 1, Dynamics and Technical Description," Lockheed Palo Alto Research Laboratory, Palo Alto, Calif., LMSC-D403329, 1974.
26. Hooker, W. W., "A Set of r Dynamical Attitude Equations for an Arbitrary n-Body Satellite Having r Rotational Degrees of Freedom," AIAA Journal, Vol. 8, No. 7, pp. 1205-1207, July 1970.
27. Hooker, W. W., and Margulies, G., "The Dynamical Attitude Equation for an n-Body Satellite," Journal of the Astronautical Sciences, Vol. XII, No. 4, pp. 123-128, 1965.
28. Huston, R. L., and Passerello, C. E., "On the Dynamics of Chain Systems", ASME Paper No. 74-WA/Aut 11.
29. Huston, R. L., and Passerello, C. E., "Dynamics of General Chain Systems," NTIS Report PB 257184, August 1976.
30. Huston, R. L., and Passerello, C. E., "On Lagranges Form of d'Alembert's Principle," The Matrix and Tensor Quarterly, Vol. 23, 1973, pp. 109-112.
31. Huston, R. L., and Passerello, C. E., "On the Dynamics of a Human Body Model," Journal of Biomechanics, Vol. 4, 1971, pp. 369-378.
32. Huston, R. L., "On the Kinematics of Large Mechanical Systems," Proceedings of the NSF Workshop on New Directions for Kinematics Research, Stanford University, August 1976.
33. Huston, R. L., and Passerello, C. E., "Eliminating Singularities in Governing Equations of Mechanical Systems," Mechanics Research Communications, Vol. 3, 1976, pp. 361-365.
34. Huston, R. L., Hessel, R. E., and Passerello, C. E., "A Three-Dimensional Vehicle-Man Model for Collision and High Acceleration Studies," SAE Paper No. 740275, 1974.

35. Huston, R. L., Hessel, R. E., and Winget, J. M., "Dynamics of a Crash Victim - A Finite Sequent Model," AIAA Journal, Vol. 14, No. 2, 1976, pp. 173-178.
36. Huston, R. L., et. al., "On Human Body Dynamics," Annals of Biomedical Engineering, Vol. 4, 1976, pp. 25-43.
37. Huston, R. L., Passerello, C. E., and Harlow, M. W., "Dynamics of Multirigid-Body Systems," Journal of Applied Mechanics, Vol. 45, No. 4, 1978, pp. 889-894.
38. Huston, R. L., and Passerello, C. E., "On Multi-Rigid-Body System Dynamics," Computer and Structures, Vol. 10, 1979, pp. 439-446.
39. Huston, R. E., and Passerello, C. E., "Multibody Structural Dynamics Including Translation Between the Bodies," Computers and Structures, Vol. 11, 1980.
40. Jerkovsky, W., "The Transformation Operator Approach to Multisystems Dynamics Part I: The General Approach," The Matrix and Tensor Quarterly, Vol. 27, No. 2, December 1976, pp. 48-59.
41. Juricic, D., and Vukobratovic, M., "Mathematical Modelling of Bipedal Walking System," ASME Paper No. 72-WA/BHF-13, 1972.
42. King, A. I., and Chou, C. C., "Mathematical Modelling, Simulation and Experimental Testing of Biomechanical System Crack Response," Journal of Biomechanics, Vol. 9, No. 5, 1976, pp. 301-317.
43. Konstantinov, M. S., and Genova, P. J., "Dynamical Point Mass Models of Spatial Mechanisms," ASME Paper No. 72-Mech-57, 1972.
44. Konstantinov, M. S., "Inertia Forces of Robots and Manipulators," Mechanism and Machine Theory, Vol. 12, 1977, pp. 387-401.
45. Kortum, W., Lehner, M., and Richter, R., "Multibody Systems Containing Active Elements: Generation of Linearized System Equations, System Analysis and Order-Reduction", Dynamics of Multibody Systems, K. Magnus, Editor, Springer, 1977, pp. 158-171.
46. Langrana, N. A., and Bartel, D. L., "An Automated Method for Dynamic Analysis of Spatial Linkages for Biochemical Applications," ASME Journal of Engineering for Industry, Vol. 97, May 1975, pp. 566-574.
47. Larson, V., "State Equations for an n-Body Spacecraft," Journal of the Astronautical Sciences, Vol. XXII, No. 1, July-September, 1974, pp. 21-35.
48. Orin, D. E., McGhee, R. B., Vukobratovic, M., and Hartoch, G., "Kinematic and Kinetic Analysis of Open-Chain Linkages Utilizing Newton-Euler Methods," Mathematical Biosciences, Vol. 43, 1979, pp. 107-130.
49. Orlandea, N., "Node-Analogous, Sparsity-Oriented Methods for Simulation of Mechanical Dynamic Systems," Ph.D. Dissertation, University of Michigan, 1973.

64. Schiehlen, W. O., and Kreuzer, E. J., "Symbolic Computerized Derivation of Equations of Motion," Dynamics of Multibody Systems, K. Magnus, Editor, Springer, 1977, pp. 290-305.
65. Stepanenko, Y. and Vukobratovic, M., "Dynamics of Articulated Open-Chain Active Mechanisms," Mathematical Biosciences, Vol. 28, No. 112, 1976.
66. Uicker, J. J., Jr., "User's Guide for IMP (Integrated Mechanisms Program): A Problem Oriented Language for the Computer-Aided Design and Analysis of Mechanisms," Report of National Science Foundation Grant GK-4552, 1973.
67. Uicker, J. J., Jr., "Dynamic Force Analysis of Spatial Linkages," Journal of Applied Mechanics, Vol. 34, 1967, pp. 418-424.
68. Uicker, J. J., Jr., "Dynamic Behavior of Spatial Linkages," Journal of Engineering for Industry, Trans. ASME, Vol. 91, 1969, pp. 251-265.
69. Uicker, J. J., Jr., Denavit, J., and Hartenberg, R. S., "An Iterative Method for the Displacement Analysis of Spatial Mechanisms," Journal of Applied Mechanics, Vol. 31, 1964, pp. 309-314.
70. Velman, J. R., "Simulation Results for a Dual-Spin Spacecraft," Proceedings of the Symposium on Attitude Stabilization and Control of Dual Spin Spacecraft, Air Force Report SAMSO-TR-68-191, Aerospace Corp. Report TR-0158 (3307-01)-16. Aerospace Corp., El Segundo, Calif., 1967.
71. Vukobratovic, M., "Dynamics of Active Articulated Mechanisms and Synthesis of Artificial Motion," Mechanisms and Machine Theory, Vol. 13, 1978, pp. 1-18.
72. Vukobratovic, M., "Computer Method for Dynamic Model Construction of Active Articulated Mechanisms Using Kinetostatic Approach," Mechanism and Machine Theory, Vol. 13, 1978, pp. 19-39.
73. Vukobratovic, M., "Synthesis of Functional Artificial Motion," Mechanism and Machine Theory, Vol. 13, 1978, pp. 41-56.
74. Vukobratovic, M., and Potkonjak, V., "Contribution of the Forming of Computer Methods for Automatic Modelling of Spatial Mechanism Motion," Mechanism and Machine Theory, Vol. 14, 1979, pp. 179-186.
75. Vukobratovic, M., and Stepanenko, Y., "Mathematical Models of General Anthropomorphic Systems," Mathematical Biosciences, Vol. 17, 1973.
76. Vukobratovic, M., Stokic, D., and Hristic, D., "New Control Concept of Anthropomorphic Manipulators," Mechanism and Machine Theory, Vol. 12, 1977, pp. 515-530.
77. Winget, J. M., and Huston, R. L., "Cable Dynamics - A Finite Segment Approach," Computers and Structures, Vol. 6, 1976, pp. 475-480.
78. Wittenburg, J., "Automatic Construction of Nonlinear Equations of Motion for Systems with Many Degrees of Freedom," Euromech 38, Coll. Springer, 1974.

50. Passerello, C. E., and Huston, R. L., "Human Attitude Control," Journal of Biomechanics, Vol. 4, 1971, pp. 95-102.
51. Passerello, C. E., and Huston, R. L., "An Analysis of General Chain Systems," NASA, CR-127924, Report No. N72-30532, 1972.
52. Paul, B., "Analytical Dynamics of Mechanisms - a Computer-Oriented Overview," Mechanism and Machine Theory, Vol. 10, 1975, pp. 481-507.
53. Paul, B., "Dynamic Analysis of Machinery via Program DYMAC," SAE Paper No. 770049, 1977.
54. Paul, B., and Krajinovic, D., "Computer Analysis of Machines with Planar Motions," Part 1 - Kinematics, Part 2 - Dynamics," Journal of Applied Mechanics, Vol. 37, 1970, pp. 797-712.
55. Potkanjak, V., and Vukobratovic, M., "Two New Methods for Computer Forming of Dynamic Equations of Active Mechanisms," Mechanism and Machine Theory, Vol. 14, 1979, pp. 189-200.
56. Roberson, R. E., and Wittenburg, "A Dynamical Formalism for an Arbitrary Number of Interconnected Rigid Bodies with Reference to the Problem of Satellite Attitude Control," Proceedings Third Congress, International Federation of Automatic Control, London, 1966, Butterworth, 1968.
57. Sadler, J. P., and Sandor, G. N., "A Lumped Parameter Approach to Vibration and Stress Analysis of Elastic Linkages," Journal of Engineering for Industry, Vol. 95, 1973, pp. 549-557.
58. Sherby, T. A., and Chmielewski, J. F., "Generalized Vector Derivatives for Systems with Multiple Relative Motion," Journal of Applied Mechanics, Vol. 35, March 1968, p. 20.
59. Sheth, P. N., "A Digital Computer Based Simulation Procedure for Multiple Degree of Freedom Mechanical Systems with Geometric Constraints," PhD Thesis, U. of Wisconsin, Madison, Wisconsin, 1972.
60. Sheth, P. N., and Vicker, J. J., Jr., "IMP (Integrated Mechanisms Program): A Computer-Aided Design Analysis System for Mechanisms and Linkages," Transactions ASME Vol. 94, Series B, Journal of Engineering for Industry, 1972, pp. 454-464.
61. Smith, D. A., Chace, M. A., and Rubens, A. C., "The Automatic Generation of a Mathematical Model for Machinery Systems," ASME Paper 72-Mech-31, 1972.
62. Russell, W. J., "The Equations for Machine Solution of the Rotational Motion of a System of Connected Bodies," Report ATM-66 9990)-48, Aerospace Corp. El Segundo, Calif., March 1966.
63. Russell, W. J., "On the Formulation of Equations of Rotational Motion for an N-Body Spacecraft," Report TR-0200 (4133)-2 Aerospace Corp., El Segundo, Calif., 1969.

79. Wittenburg, J., Dynamics of Systems of Rigid Bodies, Teubner, Leitfäden der Angewandten Math. u. Mech., Bd. 33, 1977.
80. Wittenburg, J., "Nonlinear Equations of Motion for Arbitrary Systems of Interconnected Rigid Bodies," Dynamics of Multibody Systems, (K. Magnus, Editor), Springer, New York, 1978, pp. 357-376.
81. Yang, A. T., "Inertia Force Analysis of Spatial Mechanisms," Journal of Engineering for Industry, Trans. ASME, Series B, Vol. 93, 1971, pp. 27-32.
82. Allev, T. L., "Equations of Motion for Flexible Bodies With Rigid, Gimballed Appendages," Aerospace Corp., ATM-75(6901-03)-24, May 1975.
83. Benedict, C. E., and Tesar, D., "Dynamic Response Analysis of Quasi-Rigid Mechanical Systems Using Kinematic Influence Coefficients," Journal of Mechanisms, Vol. 6, 1971, pp. 383-403.
84. Bodley, C. S. and Park, C., "The Influence of Structural Flexibility on the Dynamic Response of a Spinning Spacecraft," AIAA Paper No. 72-348, 13th Structures, Structural Dynamics and Materials Conference, San Antonio, Texas, 1972.
85. Boland, P., Samin, J. C., and Willems, P. Y., "Stability Analysis of Interconnected Deformable Bodies in a Topological Tree," AIAA Journal, Vol. 12, No. 8, August 1974, pp. 1025-1030.
86. Book, W. J., "Analysis of Massless Elastic Chains with Servo Controlled Joints," Journal of Dynamic Systems Measurement and Control, Vol. 101, September 1979, pp. 187-192.
87. Book, W. J., Malzsa-Neto, O., and Whitney, D. E., "Feedback Control of Two Beam, Two Joint Systems with Distributed Flexibility," Journal of Dynamic Systems Measurement and Control, December, 1975, pp. 424-431.
88. Brown, D. L., Allemang, R. J., and Zimmerman, R., "Parameter Estimation Techniques for Modal Analysis," SAE Paper No. 790221, 1979.
89. Canavin, J. R., and Likins, P. W., "Floating Reference Frames for Flexible Spacecraft," Journal of Spacecraft and Rockets, Vol. 14, No. 12, December 1977, pp. 724-732.
90. Castro, R., "An Experimental Design and Study of a Flexible Manipulator," MS Thesis, UCLA, 1976.
91. Dubowsky, S., "Kinematics: A Basis for High Quality Dynamic Analysis - With an Application to the Dynamics and Control of Flexible Manipulators", Proceedings of the Workshop on New Directions in Kinematic Research, NSF, Stanford, Calif., August 1976.



92. Dubowsky, S., "The Impact of System Nonlinearities and Flexibility on the Dynamic Performance of Computer Based Manipulator Control Systems," Proceedings of the Workshop on Robotic Manipulators, NSF, University of Florida, February 1978.
93. Dubowsky, S., "On Predicting the Dynamic Effects of Clearances in Planar Mechanisms," Journal of Engineering for Industry, Vol. 95, February 1974, pp. 317-323.
94. Dubowsky, S., and Freudenstein, F., "Dynamic Analysis of Mechanical Systems with Clearances, Part I: Formation of Dynamic Model: Part II: Dynamic Response," Journal of Engineering for Industry, Vol. 93, February 1971, pp. 305-316.
95. Dubowsky, S., and Gardner, T. N., "Dynamic Interactions of Link Elasticity and Clearance Connections in Planar Mechanical Systems," Journal of Engineering for Industry, Vol. 97, May 1975, pp. 652-661.
96. Dubowsky, S., and Gardner, T. N., "Design and Analysis of Multi-Link Flexible Mechanism with Clearance Connections," Journal of Engineering for Industry, February 1977, pp. 88-96.
97. Dubowsky, S., and Grant, J. L., "Application of Symbolic Manipulation to Time Domain Analysis of Nonlinear Dynamic Systems," Journal of Dynamic Systems, Measurement, and Control, Vol. 97, March 1975, pp. 60-68.
98. Dubowsky, S., and Moening, M. F., "An Experimental and Analytical Study of Impact Forces in Elastic Mechanical Systems with Clearances," Mechanism and Machine Theory, Vol. 13, 1978, pp. 451-465.
99. Dubowsky, S., and Young, S. C., "An Experimental and Analytical Study of Connection Forces in High-Speed Mechanisms," Journal of Engineering for Industry, Vol. 97, November, 1975, pp. 1166-1174.
100. Earles, S. W. E., and Wu, C. L. S., "Motion Analysis of a Rigid-Link Mechanism with Clearance at a Bearing, Using Lagrangian Mechanics and Digital Computation," Mechanisms 1972, Institution of Mechanical Engineers, London, England, 1973, pp. 83-89.
101. Erdman, A. G., Sandor, G. N., and Oakberg, R. G., "A General Method for Kineto-Elastodynamic Analysis and Synthesis of Mechanisms", Journal of Engineering for Industry Trans ASME, Vol. 94, 1972, pp. 1193-1205.
102. Fleischer, G. E., and McGlinchley, L. F., "Viking Thrust Vector Control Dynamics Using Hybrid Coordinates to Model Vehicle Flexibility and Propellant Slosh", AAS Paper No. 71-348, Astrodynamics Specialist Conference, Ft. Lauderdale, Florida, 1971.
103. Fossman, R., and Sorensen, A. Jr., "Influence of Flexible Connections on Response Characteristics of a Beam", ASME Paper No. 79-WA/DE-2, 1979.

104. Gevarter, W. B., "Basic Relations for Control of Flexible Vehicles", AIAA Journal, Vol. 8., 1970, pp. 666-678.
105. Goodman, T. P. "Dynamic Effects of Backlash", Machine Design, Vol. 35, May, 1963, pp. 150-157.
106. Ho, J. Y. L., "Direct Path Method for Flexible Multibody Spacecraft Dynamics", Journal of Spacecraft and Rockets, Vol. 14, No.2, February, 1977, pp. 102-110.
107. Ho, J. Y. L., "The Direct Path Method for Deriving the Dynamic Equation of Motion of a Multibody Flexible Spacecraft with Topological Tree Configuration", Lockheed Missiles and Space Company Technical Report D35-6977, June, 1973, AIAA Paper No. 74-786, AIAA Mechanics and Control Flight Conference, 1974.
108. Ho, J. Y. L. and Gluck, R. "Inductive Methods for Generating the Dynamic Equations of Motion for Multibody Flexible Systems Part 2", Synthesis of Vibrating Systems, ASME, 1971.
109. Hooker, W. W., "Equations of Attitude Motion of a Topological Tree of Bodies, the Terminal Members of which may be Flexible", Lockheed Missiles and Space Co. Report LMSC-D354938.
110. Hooker, W. W., "Equation of Motion for Interconnected Rigid and Elastic Bodies: A Derivation Independent of Angular Momentum", Celestial Mechanics, Vol. II, No. 3, May 1975, pp.337-359.
111. Hughes, P. C., "Modal Identities for Elastic Bodies with Application to Vehicle Dynamics and Control", ASME paper No. 79-WA/APM-34, 1979.
112. Hurty, W. C., "Dynamics Analysis of Structural Systems Using Component Modes", AIAA Journal, Vol. 3, No. 4, 1965, pp.678-685.
113. Hurty, W. C., Collins, J. D. and Hart, G.C., "Dynamic Analysis of Large Structures by Modal Synthesis Techniques", Computers and Structures, Vol. 1., 1971, pp.535-563.
114. Imam, I., Sandar, G.N. and Kramer, S. N., "Deflection and Stress Analysis in High Speed Planar Mechanisms with Elastic Links", Journal of Engineering for Industry, Transactions ASME, Vol. 95, 1973, pp.541-548.
115. Jerkovsky, W., "Exact Equations of Motion for a Deformable Body," Aerospace Corp., SA,SO-TR-77-133, March, 1977.
116. Johnson, R. C., "Impact Forces in Mechanisms," Machine Design, Vol. 30, June, 1958, pp.138-146.
117. Klosterman, A. L., and Lemon, J. R., "Building Block Approach to Structural Dynamics," ASME Paper No. 69 V1BR-30, 1969.
118. Likins, P.W., "Dynamics and Control of Flexible Space Vehicles," Technical Report 32-1329, Revision 1, Jet Propulsion Laboratory, 1970.

119. Likins, P.W., "Dynamic Analysis of a System of Hinge-Connected Rigid Bodies with Nonrigid Appendages", International Journal of Solids and Structures, Vol.9, 1973, pp. 1473-1487.
120. Likins, P.W., "Finite Element Appendage Equations for Hybrid Coordinate Dynamic Analysis," International Journal of Solids and Structures, Vol. 8., 1972, pp. 709-731.
121. Likins, P.W., "Analytical Dynamics and Nonrigid Spacecraft Simulation," Technical Report 32-1593, Jet Propulsion Laboratory, 1974.
122. Likins, P.W., "Quasi-Coordinate Equations for Flexible Spacecraft," AIAA Journal, Vol. 13, 1975, pp.524-526.
123. Likins, P.W., and Bouvier, H. K., "Attitude Control of Nonrigid Spacecraft," Aeronautics and Astronautics, Vol. 9, No. 5, 1971.
124. Livermore, D. F., "The Determination of Equilibrium Configurations of Spring Restrained Mechanisms Using (4x4) Matrix Methods," Journal of Engineering for Industry, Vol. 89, February, 1967.
125. Lower, G. G., and Jandrasits, W. G., "Survey of Investigations into the Dynamic Behavior of Mechanisms Containing Links with Distributed Mass and Elasticity," Mechanism and Machine Theory, Vol. 7., No. 1, 1972, pp. 3-17.
126. Mansour, W. M., and Townsend, M. A., "Impact Spectra and Intensities for High-Speed Mechanisms," Journal of Engineering for Industry, Vol. 97, February, 1975, pp.347-353.
127. Mansour, W. M. and Townsend, M. A., "A Pendulating Model for Mechanisms with Clearance in the Revolute," Journal of Engineering for Industry, Vol. 97, February, 1975, pp.354-358.
128. Margolis D. L., and Karnopp, D. C., "Bond Graphs for Flexible Multibody Systems," Journal of Dynamic Systems Measurement, and Control, Vol. 101, No. 1, 1979, pp: 50-57.
129. Modi, V. J., " Attitude Dynamics of Satellites with Flexible Appendages-A Brief Review," Journal of Spacecraft and Rockets, Vol. 11, No. 11, 1974.
130. Maatuk, J., "A Study of the Dynamics and Control of Flexible Spatial Manipulators", Ph.D. Dissertation, UCLA, 1976.
131. Moening, M. F., " An Experimental and Analytical Study of an Elastic Mechanical System with Clearances," MS Thesis, UCLA, 1976.
132. Ness, D. J. and Farrenkopt, R. L., "Inductive Methods for Generating the Dynamic Equations of Motion for Multibodied Flexible Systems, Part 1: Unified Approach," Synthesis of Vibrating Systems, ASME, 1971, New York,
133. Neubauer, A. H., Jr., "An Analytical Study of the Dynamics of an Elastic Linkage," Journal of Engineering for Industry, August, 1966, pp.311-317.

134. Park, K. C., and Saczalski, K. J. "Transient Response of Inelastically Constrained Rigid-Body Systems," ASME Engineering for Industry, Vol. 96, August, 1974, p. 1041-1047.
135. Roberson, R. E., "A Form of the Translational Dynamical Equations for Relative Motion in Systems of Many Non-Rigid Bodies," Acta Mechanica, Vol. 14., 1972, pp.297-308.
136. Roberson, R. E., (Editor), Lectures on Dynamics of Flexible Spacecraft, Dubrovnik, Sept., 1971, Centre Internationale des Sciences Me'caniques, Udine, 1971
137. Sergeyev, V.I., and Yudin, K.M., "On a Model for Mechanisms with Clearances," (in Russian) Mechanical Science Journal of the Soviet Academy of Sciences, No. 5, 1970.
138. Sutherland, G. H., "Analytical and Experimental Investigation of a High Speed Elastic-Membered Linkage," Journal of Engineering for Industry, May, 1975, pp. 542-550.
139. Valero, R. A., "Dynamic Analysis of Planar Nonlinear Mechanical Systems with Connection-Elasticity and Clearances", MS Thesis, UCLA, 1977.
140. Viscomi, B. V., and Ayre, R. S., "Nonlinear Dynamic Response of Elastic Slider-Crank Mechanism," Journal of Engineering for Industry, February, 1971, pp.251-262.
141. Windrey, R. C., "Elastic Link Mechanisms Dynamics", Journal of Engineering for Industry, Trans ASME Vol. 93, 1971, pp.268-272.
142. Winfrey, R. C., Anderson, R. V., and Ghilka, C. W., "Analysis of Elastic Machinery with Clearances," Journal of Engineering for Industry, Vol. 95, August, 1973, pp.695-703.
143. Yudin, K. M., "A Study of Dynamic Model of Mechanism with Clearances," (in Russian), Mechanical Science Journal of the Soviet Academy of Sciences, No. 2, 1971, pp. 58-60.
144. Kane, T. R., "Dynamics of Nonholonomic Systems," ASME Journal of Applied Mechanics, Vol. 28, 1961, pp. 574-578.
145. Kane, T. R., Dynamics, Holt, Rinehart, and Winston, New York, 1968
146. Paul, B., Kinematics and Dynamics of Planar Machinery, Prentice Hall, 1979.
147. Whittaker, E. T., Analytical Dynamics, Cambridge, London, 1937
148. Kane, T. R., and Likins, P.W., "Kinematics of Rigid Bodies in Space-flight," Stanford University, Applied Mechanics Report No. 204, 1971, pp. 26, 119.

149. Kane, T. R., and Wang, C. F., "On the Derivation of Equations of Motion," Journal of the Society for Industrial and Applied Mathematics, Vol. 13, 1965, pp. 487-492.
150. Brand, L., Vector and Tensor Analysis, Wiley, New York, 1947.
151. Martin, H. C., Introduction to Matrix Methods of Structural Analysis, McGraw Hill, New York, 1966.
152. Huston, J. C., Passerello, C. E., and Huston, R. L., "Numerical Prediction of Head/Neck Response to Shock-Impact" Measurement and Prediction of Structural and Biodynamic Crash-Impact Response, ASME, 1976, pp. 137-150.
153. Huston, R. L., Winget, J. M., and Harlow, M. W., "A Biodynamic Model of a Parachutist", Aviation, Space and Environmental Medicine, Vol. 49, January, 1978, pp. 178-182.
154. Huston, J. C., Huston, R. L., and Harlow, M. W., "A Comprehensive, three-Dimensional Head-Neck Model for Impact and High Acceleration Studies", Aviation, Space and Environmental Medicine, Vol. 49, January, 1978, pp. 205-210.
155. Huston, R. L., and Sears, J., "Effect of Protective Helmet Mass on Head-Neck Dynamics", ASME 1979 Biomechanics Symposium, AMD Vol. 32, pp. 227-229.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ONR - UC - ES - 040180 - 8 /	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Multi-body Dynamics Including the Effects of Flexibility and Compliance		5. TYPE OF REPORT & PERIOD COVERED Technical 9/30/78-2/29/80
7. AUTHOR(s) Ronald L. Huston		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS University of Cincinnati Cincinnati, Ohio 45221		8. CONTRACT OR GRANT NUMBER(s) N00014-76-C-0139
11. CONTROLLING OFFICE NAME AND ADDRESS ONR Resident Research Representative Ohio State University 1314 Kenner Rd., Columbus, Ohio 43212		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 122303
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Office of Naval Research Structural Mechanics Code Department of the Navy Arlington, Virginia 22217		12. REPORT DATE 4/1/80
		13. NUMBER OF PAGES 57
		15. SECURITY CLASS. (of this report) Unclassified
16. DISTRIBUTION STATEMENT (of this Report)  Distribution of this report is unlimited		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  Chain Link Modelling, Finite Segment Modelling, Robotics, Compliance, Dynamics, Multi-body Systems, Kinematics		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  New and recently developed concepts and ideas useful in obtaining efficient computer algorithms for solving the equations of motion of multi-body mechanical systems with flexible links are presented and discussed. These ideas include the use of Euler parameters, Lagrange's form of d'Alembert's principle, generalized speeds, quasi-coordinates, relative coordinates, structural analysis techniques and body connection arrays. The mechanical systems considered are linked bodies forming a tree structure, but with no "closed loops" permitted. An explicit formulation of the equations of motion is presented.		

DD FORM 1473

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-014-6001

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)